WMHS-0101-CHV - Wall Mount Hand Spray

Outdoor Shower Company, LLC. Dallas, Georgia www.outdoorshowerco.com—1-866-shower1







WMHS-0101-CHV PARTS LIST:

ome Plated Brass Cross Handle Angle Valve - 1/2" FIP
on Adapter - 1/2" - 14 NPT Female Inlet–Chrome Plated
' Stainless Steel Coupling
'X 2" Stainless Steel Nipple
nd Spray Bracket with Ring - 1/4" Stainless Steel Rod
nd Spray & 60" Stainless Steel Hose



Accessories can vary due to availability and slight modifications by the manufacturer. Some parts may be upgraded or substituted at customer's request.

WMHS-0101-CHV Installation Guidelines

Recommended Water Supply Connection Height: 42"-48"

Threads of 1/2" MIP Supply Line should be exposed through wall.

- 1. With about 1" of water line threads exposed, connect angle valve to pipe using Teflon tape.
- 2. **<u>NOTE</u>**: Flush supply lines before installing valve.
- 3. Attach nipple to valve using Teflon tape.
- 4. Slide hand spray bracket ring onto nipple.
- 5. Attach coupling to nipple using Teflon tape.
- 6. Attach hose to coupling using Teflon tape.